



5588E-U
(Desktop Reader)

Features

- Desktop Card reader
- Easy to use with no driver required.
- USB plug and play.
- Cursor output..
- No need for integrated development
- Good compatibility supports Windows, Linux operating systems.
- Directly powered from the USB port.
- 5588 series is manufactured in KEYKING's ISO:9001 registered facility.

5588E-U can be easily disinfected in areas where hygiene is important, and has an exceptionally long life due to no moving parts. The unit resists the elements such as glue, oil, rain, ice, snow. Ideal for hospitals, industrial and commercial application.

This dual-application product has advanced reader features for wide compatibility with different controller types including multiple RFID card transmission formats, LED & Buzzer control.

Specifications

- Maximum read range: 5-15cm
- Modulation: ASK at 125 kHz
- Reading Protocol: Manchester Code
- Operating Voltage: USB Power, 5VDC
- Reading speed: <0.2s
- Communication Distant: 1M
- Communication Port : USB
- Working Temperature: -30°C to 65°C
- LED Control Input: Dry Contact, Normally Open
- Buzzer Control Input: Dry Contact, Normally Open
- Dimensions: 100mm L x 140mm W x 30mm D
- Weight: 400 g



KEYKING TECH LIMITED

Add: 5F, Keyking Building, 12th, Shangwei Industrial No.1 Road, Zhangkengjing, Guanhu Town, Longhua New District, Shenzhen, China, 518110.

Tel: (86)755-8829 9009 Fax: (86)755-8829 9004 Website: www.keyking.net