

**6610P-4****Features:**

- Smooth attractive design, with all-weather
- Blue backlight convenient to night use
- The management software can directly change the reader's address
- Light and buzzer control indicate the difference between illegal and legal cards
- 1 Led with 2 colors and integral sounder for programming
- Data transmission: OSDP output, safe and reliable, transmission distance up to 1200 meters
- Manufactured in ISO:9001 registered facility

Description:

This superior quality smart reader is rugged, weather-resistant and attractive in design. The product was designed to reduce stock levels. Blue backlight assist operation in low or no light conditions. With the internal sounder, 6610P-4 provides superior accessibility.

6610P-4 can be easily disinfected in areas where hygiene is important, and has an exceptionally long life due to no moving parts. The unit resists the elements such as glue, oil, rain, ice, snow. Ideal for hospitals, industrial and commercial application.

This dual-application product has advanced reader features for wide compatibility with different controller types including multiple RFID card transmission formats, LED & Buzzer control.

Specifications:

- Maximum Read Range: **120mm**
- Modulation: 125KHz
- Compatible Cards: AWID, EM, HID, KK
- Output: OSDP Transmission Protocol Based on RS485, 4 Wires
- Distance to Panel: 1,200m
- Operating Voltage: 7 ~ 12VDC
- Operating Current: ≤100mA
- Standby Current: ≤50mA
- Working Environment: -30°C ~ 65°C (-22°F to 150°F), 0 ~ 95%RH
- LED Control Input: OSDP Protocol
- Buzzer Control Input: OSDP Protocol
- Dimensions: 86(L) x 43(W) x 21(D)mm
- Weight: **85 g**

**KEYKING GROUP LIMITED**

B10/F, Keyking Building, 12th, Shangwei Industrial No.1 Road, Zhangkengjing, Guanhu Town, Longhua New District, Shenzhen, China, 518110.

Tel: (86)755-8829 9009 Fax: (86)755-8829 9004 Website: www.keyking.net