

**6611KU**

(Mifare Card Reader)

Features

- Supports PIN + CARD credentials.
- Smooth attractive design, indoor use only
- Blue LED as normal.
- Blue Background
- OLED display which can be defined
- Company name and Clock on the display
- 1 LED with 2 colors and integral sounder for programming and operation.
- Green connector for wiring.
- Multi Mode: Mifare SN, Mifare Sector, CPU card.
- Supports all M-1, S50, S70, KK1208M1 or Compatible cards.
- 6611KU is manufactured in SECUSYS's ISO: 9001 registered facility.

Description

This superior quality Proximity reader is rugged, weather-resistant and attractive in design. The product was designed to reduce stock levels. Blue backlit LED assist operation in low or no light conditions. With the internal sounder, 6611KU provides superior accessibility.

6611KU can be easily disinfected in areas where hygiene is important, and has an exceptionally long life due to no moving parts. The unit resists the elements such as glue, oil, rain, ice, snow. Ideal for hospitals, industrial and commercial application.

This dual-application product has advanced reader features for wide compatibility with different controller types including multiple RFID card transmission formats, LED & Buzzer control.

Specifications

- Maximum read range: 50mm
- Modulation: ASK at 13.56M kHz
- Compatible cards: Mifare S50, S70, KK1208M1 CPU cards
- Output: W26/34 Options
- Door Bell: dry contact
- Operating Voltage: 7-12VDC
- Operating Current: $\leq 100\text{mA}$
- Standby Current: $\leq 80\text{mA}$
- Working Temperature: -30°C to 65°C (-22°F to 150°F)
- Operating Humidity: 0 to 95%
- LED Control Input: Dry Contact, Normally Open
- Buzzer Control Input: Dry Contact, Normally Open
- Dimensions: 126mm L x 95mm W x 25mm D
- Weight: 290 g (0.63 lbs)

**KEYKING GROUP LIMITED**

Add: 5F, Keyking Building, 12th, Shangwei Industrial No.1 Road, Zhangkengjing, Guanhu Town, Longhua District, Shenzhen, China, 518110.

Tel: (86)755-8829 9009 Fax: (86)755-8829 9004 Website: www.keyking.net