KEYKING
Integrated Security System

Proximity Reader
sounder, 6630P provides superior accessibility.
6630P
Integrated Security Solutions

6630P
(Proximity Reader)

6630P can be easily disinfected in areas where hygiene is important, and has an exceptionally long life due to no moving parts. The unit resists the elements such as glue, oil, rain, ice, snow，ideal for hospitals, industrial and commercial application.

This dual-application product has advanced reader features for wide compatibility with different controller types including multiple RFID card transmission formats, LED & Buzzer control.

Features

- Smooth attractive design, Elegant.
- Blue LED as normal.
- 1 LED with 2 colors and integral sounder for programming and operation.
- Green connector or cable for wiring. ● Built-in EM Reader
- 6630P is manufactured in keyking's ISO:9001 registered facility.

Description

This superior quality Proximity reader is rugged, weather-resistant and attractive in design. Blue backlit LED assist operation in low or no light conditions. With the internal

Specifications

- Maximum read range: 80mm (6.00 in.) ● Modulation: ASK at 125KHz ● Compatible cards: AWID/EM/HID/KKID.
- Output: W26/34 Options
- Door Bell: dry contact ● Operating Voltage: 7-12VDC ● Operating Current: ≤100mA
- Standby Current:≤80mA
- Working Temperature: -30°C to 65°C (-22°F to 150°F)
- Operating Humidity: 0 to 95% ● LED Control Input: Dry Contact, Normally Open
- Buzzer Control Input: Dry Contact, Normally Open
- Dimensions: 90mm L x 90mm W x 25mm D
- Weight: 200 g

KEYKING TECH LIMITED
Add: 5F, Keyking Building, 12th, Shangwei Industrial No.1 Road, Zhangkengjing, Guanhu Town, Longhua New District, Shenzhen, China, 518110.