



AVR6619KP

Feature:

- Supports PIN + Card credentials.
- Smooth attractive design, with all weather
- Blue backlit and anti-vandal metal construction
- 2 LED and integral sounder for programming and operation
- Optical tamper detection technology
- 6-wire shielded interface cable
- 8 programmable PIN transmission modes including options for key stream, binary, parity, and 3x4 matrix.
- Supports Wiegand 26/34-Bit, or Clock & Data RFID card transmission formats
- AVR6619KP is manufactured in KEYKING's ISO: 9001 registered facility

Description:

AVR6619KP is an anti vandal proximity card reader which is rugged, weather-resistant and attractive in design. Its blue backlit keys assist operation in low or no light conditions. AVR6619KP provides superior accessibility with the internal sounder.

AVR6619KP can be easily disinfected in areas where hygiene is important, and has an exceptionally long life due to no moving parts. The unit resists the elements such as glue, oil, rain, ice, snow. Ideal for hospitals, industrial and commercial application.

This dual-application product has advanced reader features for wide compatibility with different controller types including multiple PIN & RFID card transmission formats, LED control and tamper detection.

Application:

office, warehouse, industrial park, schools, communities, hotels, public service places, etc.

Specification:

- Maximum Read Range: 80mm
- Modulation: ASK at 125 KHZ
- Compatible Cards: HID, AWID, KKID, EM
- Operating Voltage: 7-15VDC
- Operating Current: ≤100mA
- Standby Current: ≤50mA
- Tamper Output: Optical Technology. Open collector, active low 32mA max sink current.
- Working Temperature: -30°C to 65°C (-22°F to 150°F)
- Operating Humidity: 0 to 95%RH
- Dimensions: 126mm L x 90mm W x 25mm D
- Weight: 490g (1.05 lbs)