



DPU-OSDP24

Features:

1. 32 bit ST ARM® Cortex M4 processor with 16MBit data memory
2. Communication Modes: TCP/IP, 10/100M Based
3. Compatible with all **OSDP** reader
4. Event Flow Control
5. Support 500 Visitors
6. Support Master + Slave Group cards
7. CE, FCC, RoHS Approval

**Series Description:**

The 1 Series of access controllers can be used in a standalone or networked configuration mode, are compatible with the 1 & 3 Series access controllers and Lift Controllers and Multi IO Controllers. The 1 Series controllers can be connected to a TCP/IP network, and work perfect with Sphinx.

Controller Description:

The **DPU-OSDP24**, (**KEYKING, OSDP Series, Door Controller, 2 Door, 4 Readers, TCP/IP Enabled**) is an economic 2 doors access controller allowing for the connection of both In and Out card readers.

Specifications:

- CPU: 32 Bit Processor
- Data Memory: 16M bit (protected)
- 2 Door Relay (NC/NO)
- 2 Door Sensor (NO)
- 2 Exit Button
- 2 Auxiliary Output Relays
- 2 Auxiliary Inputs
- Reader: 4 pcs **OSDP** Readers
- TCP/IP, 10/100M Based
- 15 Time Groups for each door
- Cardholder Capacity: 30,000 users, **can be expanded to 100,000 users**
- Transaction Storage: 200,000 events, **can be expanded to 500,000 events**
- Maximum LAN Distance: 1200 meters (4000ft) using RS485.
- Operating Voltage: 12V DC ($\pm 10\%$)
- 110/220 AC (50/60HZ) switched mode 12V DC 6A Power Supply c/w 13.8V DC battery charging circuit (Charging Inspector)
- Operating Current: $\leq 200\text{mA}$
- Standby Current: $\leq 150\text{mA}$
- Working Temperature: $-40^{\circ}\text{C} \sim 70^{\circ}\text{C}$
- 1 Lithium battery backup (up to 10 years data retention)
- Metal case dimensions: 315mm x 205mm x 55mm
- Weight: 0.2Kg (without metal case)
2.7Kg (with metal case & PSU)

KEYKING GROUP LIMITED

Add: 5F, Keyking Building, 12th, Shangwei Industrial No.1 Road, Zhangkengjing, Guanhu Town, Longhua New District, Shenzhen, China, 518110.

Tel: (86)755-8829 9009 Fax: (86)755-8829 9004 Website: www.keyking.net