



IMM707

**Feature:****Industrial Chip Platform And System**

- Built-in industrial chip, Linux operating system to achieve high stability

**Visual Intercom**

- Support two-way voice intercom between indoor machine or central management machine

**Voice Broadcast**

- Built-in high sound quality speaker, support voice broadcast

**Receive Message**

- Support receiving message from community property, call records, alarm records

**Call Property**

- Support one-click to call property management

**Access Control**

- Support video intercom with entrance machine and open door remotely

**Video Surveillance**

- Monitoring the entrance machine and authorized public camera

**Search Record**

- Support door open and call record management

**Alarm**

- Receive and show alarm information of users in real time

**Description:**

IMM707 Face recognition based on the Linux system platform of industrial chip, embedded intelligent deep learning face recognition technology, integrate face detection, tracking, capture, feature extraction, recognition and other intelligent analysis, with high recognition rate, fast speed, support real-time voice broadcast.

**Application:**

Smart communities, schools, office buildings, hospitals etc.

**Specification:****1. Hardware**

- Display: 7 inch HD touch screen , resolution 1024\*600
- CPU: High performance industrial chip , Linux operation system
- Loudspeaker: 8Ω, 0.5W
- Microphone: Inbuilt microphone
- Material: CNC aluminium alloy cover

**2. Network**

- Support LAN
- Protocol: TCP/IP, ICMP, HTTP, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP
- IP Address: Fixed IP, Dynamic IP

**3. Video/Audio**

- Video Compression Standard: H.264
- Video Frame Rate: 25F/s
- Audio Compression Format: G.711u

**4. Interface**

- Power Input: 1 PCS 12VDC
- Power Output: 1 PCS 12VDC(200mA), 1 PCS 5VDC(500mA)
- Defense Alarm: 4 PCS
- Emergence Alarm: 1 PCS
- Wiegand Output: 1 PCS
- TCP/IP: 10/100M adaptive

**5. Environment**

- Power Supply: 12VDC
- Power Consumption: ≤3.5W
- Temperature: -30℃~60℃
- Humidity: ≤95%
- Dimension: 220(W)\*135.6(H)\*17.7mm(D)
- Weight: 460g(with bracket)
- Installation: Wall mounted