



MR600U

(Magnetic & CPU Smart Reader)

Features

- Smooth attractive design, with all-weather
- Blue backlit.
- 1 LED with 2 colors and integral sounder for programming and operation.
- Green connector for wiring.
- Multi Mode: Mifare SN, Mifare Sector, CPU card.
- Communication Encryption: 3DES
- RS485 output, private protocol.
- MR600U is manufactured in KEYKING's ISO:9001 registered facility.

Description

This superior quality Smart reader is rugged, weather-resistant and attractive in design. The product was designed to reduce stock levels. Blue backlit LED assist operation in low or no light conditions. With the internal sounder, MR600U provides superior accessibility.

MR600U can be easily disinfected in areas where hygiene is important, and has an exceptionally long life due to no moving parts. The unit resists the elements such as glue, oil, rain, ice, snow. Ideal for hospitals, industrial and commercial application.

This dual-application product has advanced reader features for wide compatibility with different controller types including multiple RFID card transmission formats, LED & Buzzer control.

Specifications

- Maximum read range*: 50mm (2.00 in.)
- Modulation: ASK at 13.56MHz
- Compatible cards: Mifare S50, S70, KK1208M1 CPU cards
- ISO14443A
- Output: RS485 & Wiegand
- Operating Voltage: 7-12VDC
- Operating Current: $\leq 100\text{mA}$
- Standby Current: $\leq 80\text{mA}$
- Working Temperature: -30°C to 65°C (-22°F to 150°F)
- Operating Humidity: 0 to 95%
- LED Control Input: RS485 protocol
- Buzzer Control Input: RS485 protocol
- Dimensions: 86mm L x 86mm W x 21mm D (6.59 in. x 6.59 in. x 0.83 in.)
- Weight: 290 g (0.63 lbs)