



Royal Series

USA Single Gang Box **Keypad** Reader



Metallic Housing
Vandal Resistant
Weather Proof – IP65



Silver or Rose Gold Housing (custom colors available)



Backlit Touchkeys and OLED Display



Large Bright Indicator – Blue / Green light



RY02KDP (RY02KDP-4)

* - Card Number Only

® - Brands and Trademarks mentioned are the property of their owners.

Features



Smart Card Reader

- Proximity, HID/Awid/EM/KKID, 125KHz;



Wiegand 26 & 34Bits Output, Field Selectable – 4-6 Wire

RS-485 output - 2 wire secured communication, up to 4000ft. distance



Low Power consumption



Single “Gang” size – USA Standard

Specification

Model	P	U
Frequency	125KHz	13.56MHz
Technology	Proximity, HID/Awid/EM/KKID, 125KHz;	HF, Mifare, Desfire, PKI Encrypted, NFC, CPU, FIPS-201*, and more
Encryption	Manchester code	3Des
Read Range	3~8 cm	2~6cm
Power	7 – 15 Vdc	
Current – No Display	≤80mA	≤80mA
Current with Display	≤150mA	≤150mA
Temperature	-4°F - 150°F	
Humidity	95% RH	
Dimension		

Reader Protocol –

4: RS-485

_ : Wiegand

Card Type

P: 125KHz – LF, TK, EM, HID Prox., AWID, and more

U: 13.56MHz – HF, NFC, Mifare, PKI Encrypted, CPU,
FIPS-201* and more

D: Desfire, WG66

Features:

_ : Card Reader Only

K: Card Reader & Keypad

KD: Card Reader with Keypad and OLED Display

Mounting

01: EU 86×86 Box

02: USA Gang Box

RY 02 KD P- 4

Network Diagram

系统图

Network

