



## Royal Series

### USA Single Gang Box Standard Reader



Metallic Housing  
Vandal Resistant  
Weather Proof – IP65



Silver or Rose Gold Housing (custom colors available)



Backlit Touchkeys and OLED Display



Large Bright Indicator – Blue / Green light



RY02U

RY02KDU

RY02KU

\* - Card Number Only

® - Brands and Trademarks mentioned are the property of their owners.

## Features



Multi-Technology Card Reader

- P: 125KHz – LF, RF, EM, TK, HID Prox., AWID and others

- U: 13.56MHz – HF, Mifare, DesFire, NFC, PKI Encrypted, CPU, FIPS-201\*



Wiegand 26 & 34Bits Output, Field Selectable – 4-6 Wire

RS-485 output - 2 wire secured communication, up to 4000ft. distance



Low Power consumption



Single “Gang” size – USA Standard

## Specification

Model	P	U
<b>Frequency</b>	125KHz	13.56MHz
<b>Technology</b>	LF, TK, EM, AWID, HID Prox. and more	HF, Mifare, Desfire, PKI Encrypted, NFC, CPU, FIPS-201*, and more
<b>Encryption</b>	Manchester	3Des
<b>Read Range</b>	~4'	~2'
<b>Power</b>	7 – 15 Vdc	
<b>Current – No Display</b>	≤50mA	≤80mA
<b>Current with Display</b>	≤80mA	≤150mA
<b>Temperature</b>	-4°F - 150°F	
<b>Humidity</b>	95% RH	
<b>Dimension</b>	2¾' × 4¾' × 1⅛'	

**RY 02 KD P 4**

### Reader Protocol –

4: RS-485

\_ : Wiegand

### Card Type

P: 125KHz – LF, TK, EM, HID Prox., AWID, and more

U: 13.56MHz – HF, NFC, Mifare, PKI Encrypted, CPU, FIPS-201\* and more

D: Desfire, WG66

### Features:

\_ : Card Reader Only

K: Card Reader & Keypad

KD: Card Reader with Keypad and OLED Display

### Mounting

01: EU 86×86 Box

02: USA Gang Box

## Network Diagram

系统图

Network

